

Power		
Power Source	Diesel	Gas
Engine	Kubota® 719 cc, 3-cylinder, industrial grade	Kawasaki 4 cycle OHV 675 cc twin-cylinder industrial grade
Engine - Cooling	Liquid	Air
Engine - Lubrication & Oil Filter Type	Full-pressure; spin-on	Full-pressure; spin-on
Max Torque	33 ft-lb (44.7Nm)	39.8 ft-lb @ 2400 fp
Horsepower	20 (14.9 kw)	23.0 @ 3600 rpm per SAE J1940/1349
Ignition	Compression	Transistorized magneto
4WD Engagement	Automatic - IntelliTrak All-Wheel-Drive	Automatic - IntelliTrak All-Wheel-Drive
Differential - Front	Automatic - IntelliTrak All-Wheel-Drive	Automatic - IntelliTrak All-Wheel-Drive
Differential - Rear	Auto locking - IntelliTrak All-Wheel-Drive	Auto locking - IntelliTrak All-Wheel-Drive
High-Low Range Engagement	Automatic	Automatic
Torque Converter	CVT	CVT
Electrical System	12-volt, 500 CCA	12-volt, 500 CCA

Agility		
Power Source	Diesel	Gas
Steering	Rack & pinion	Rack & pinion
Tilt Steering Wheel	Standard	Standard
Suspension - Front	Independent double A-arms w/ coil-over shocks	Independent double A-arms w/ coil-over shocks
suspension - Rear	Swing arm w/ coil-over shocks	Swing arm w/ coil-over shocks
Brakes	4-wheel, hydraulic disc	4-wheel, hydraulic disc
Park Brake	Foot-operated	Foot-operated

Strength / Design		
Power Source	Diesel	Gas
Frame Chasis	Rust-proof non-corrosive, aircraft-grade 6061 aluminum frame	Rust-proof non-corrosive, aircraft-grade 6061 aluminum frame
Body - Front	High-impact, scratch-resistant, GE Geloy injection molded	High-impact, scratch-resistant, GE Geloy injection molded

	color	color	
Body - Rear	Rugged, scratch-resistant injection molded plastic	Rugged, scratch-resistant injection molded plastic	
Tires - Front	Mud, 25 x 11-12, 4-ply, (optional all-terrain tires)	Mud, 25 x 11-12, 4-ply, (optional all-terrain tires)	
Tires - Rear	Mud, 25 x 11-12, 4-ply, (optional all-terrain tires)	Mud, 25 x 11-12, 4-ply, (optional all-terrain tires)	
Instrumentation	Electronic fuel gauge/hour meter, low oil warning light (speedometer optional)	Electronic fuel gauge/hour meter, low oil warning light (speedometer optional)	
Cargo Box Size	48 x 49.8 x 10.9 in (121.9 x126.5 x 27.7 cm)	48 x 49.8 x 10.9 in (121.9 x126.5 x 27.7 cm)	
Bed Height	33 in (83.8 cm)	33 in (83.8 cm)	
Bed Capacity	800 lb (362.9 kg)	800 lb (362.9 kg)	
Seating Capacity	Bench (standard)/bucket in either the first or second row (available)	Bench (standard)/bucket in either the first or second row (available)	
Total Vehicle Capacity	1,600 lb (725.7 kg)	1,600 lb (725.7 kg)	
Overall Length	157.6 in (400.3 cm)	157.6 in (400.3 cm)	
Overall Width	60 in (152.4 cm)	60 in (152.4 cm)	
Overall Height	78.6 in (199.6 cm)	78.6 in (199.6 cm)	
Wheelbase	114 in (289.6 cm)	114 in (289.6 cm)	
Ground Clearance	7.4 in (18.8 cm)	7.4 in (18.8 cm)	
Ground Clearance Under Foot Platform	12.1 in (30.7 cm)	12.1 in (30.7 cm)	
Fuel Tank Capacity	6.5 gal (24.6 L)	6.5 gal (24.6 L)	
Tread (Front/Rear)	48.8 in (124 cm)/48.8 in (124 cm)	48.8 in (124 cm)/48.8 in (124 cm)	
Dry Weight Less Batteries	1,786 lb (810.1 kg)	1,605 lb (728 kg)	
Turning Radius	17.7 ft (5.4 m)	17.7 ft (5.4 m)	

Vehicle
Warranty

2-year/2,000-
hour, limited

2-year/2,000-
hour, limited

