

<b>Power</b>	
Power Source	Gas
Engine	Kawasaki 4-cycle, OHV, 351 cc, single cylinder, air-cooled, pressure-lubricated, spin-on oil filter
Horsepower	11.5 @ 3,600 rpm , exceeds SAE J1940 Performance Standards.
Governor	Automatic ground speed sensing, internally geared-in unitized transaxel
Governed RPM	2900+/- 30
Ignition	Electronic w/electronic limiter
Drive Unit	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
Electrical System	12-volt, 500 CCA 105 min. reserve

<b>Agility</b>	
Power Source	Gas
Steering	Self-adjusting rack & pinion
Suspension - Front	Independent leaf spring with dual hydraulic shocks
suspension - Rear	Leaf springs with dual hydraulic shocks
Brakes	Four-wheel mechanical drum
Park Brake	Foot-operated, multi-lock
Stabilizer Bar	Yes

<b>Strength / Design</b>	
Power Source	Gas
Frame Chasis	Rust-proof non-corrosive, aircraft-grade 6061 aluminum frame
Body - Front	ArmorFlex®
Body - Rear	All aluminum
Body Finish	Matching paint over molded in color
Light Package	Dual halogen headlights
Trailer Hitch	Standard
Tires - Front	22 x 11.00-10, 6-ply rated, heavy-duty all-terrain tread
Tires - Rear	22 x 11.00-10, 6-ply rated, heavy-duty all-terrain tread
Instrumentation	Electronic fuel gauge/hour meter, low-oil warning light
Cargo Box Size	48.8 x 49.8 x 10.9 in (123.8 cm x 126.4 cm x 27.6 cm)
Flat Bed Size	46.9 in x 48.3 in (119.1 cm x

	122.7 cm)	
Bed Height	27.5 in (69.9 cm)	
Bed Capacity	500 lb. (226.8 kg)	
Total Vehicle Capacity	900 lb. (408.2 kg)	
Overall Length	120.4 in (305.8 cm)	
Overall Width	51.3 in(130.2 cm)	
Overall Height	51.1 in (129.8 cm)	
Wheelbase	78.5 in (199.4 cm)	
Ground Clearance	6.4 in (16.3 cm)	
Fuel Tank Capacity	7.0 gal (26.5 Liters)	
Tread (Front/Rear)	36.5 in/41.3 in (92.7 cm/104.8 cm)	
Dry Weight Less Batteries	910 lb. (412.8 kg)	
Maximum Speed	15-17 mph (24.1-27.4 kph)	
Outside Radius Circle	21.7 ft (6.6 m) dia.	
Turning Radius	10.8 ft (3.3 m)	
Intersecting Aisle Radius	77.0 in (195.6 cm)	
Vehicle Warranty	2-year/2000 hour limited	